

# currenza <sup>c</sup><sup>2</sup>

CHANGER

## The Ultimate Coin Management Solution



**Reliability.** The Currenza<sup>®</sup> c<sup>2</sup> directly measures the coins in each tube using 4 optical sensors. It “sees” coins at 100%, 75%, 40%, 8% levels without false readings. The c<sup>2</sup>'s Eclipse Pin Technology introduces a new standard in dispense reliability by firmly engaging the coin to prevent slipping. Currenza<sup>®</sup> c<sup>2</sup> is the only coin changer with a triple motor payout dispenser delivering the ultimate in payout reliability and speed. Single motor vulnerability is a thing of the past.

**Security.** The Currenza<sup>®</sup> c<sup>2</sup> uses our patented new sensor system and 40 measurements of coin parameters.

**Maximize your profits.** The c<sup>2</sup>'s industry leading payout speed (6 Coins per second) and flexible change configuration keep the sales rolling in. Easy cassette removal for replenishment and simple display operation make service times shorter. The higher coin capacity allows longer intervals between replenishment. Most important is a driver should never service a machine because it ran out of change, when the machine still had available products. That is what high change capacity is about.

**Best in Coin Management.** The Currenza<sup>®</sup> c<sup>2</sup> Coin Changer is designed to minimize problems, but should one occur it automatically reacts to any tube failure by redirecting coins around the problem. Further it has:

- Industry's widest temperature range -25°C to +80°C  
- Las Vegas summers to winters in Maine
- Full audit detail available via the display
- Optimizes coin inventory
- Simple menus to audit, configure and diagnose



# Currenza <sup>c<sup>2</sup></sup> CHANGER

The Currenza® c<sup>2</sup> Coin Changer has a wide array of capabilities to maximize your sales and minimize your costs. c<sup>2</sup> comes as a 6-tube changer including a full graphical display. You can configure, audit and run diagnostics with no additional tools. The design is based on our experience of more than 50 years of coin handling. Currenza® c<sup>2</sup> is a member of a new global product family that has the reliability, security, and flexibility assuring your investment performs for years to come. As prices change and new coins are introduced, c<sup>2</sup> provides the greatest flexibility to meet new requirements.

## Functional Capabilities

- ✓ 6 self-replenishing tubes
- ✓ 3 Independent Dispense motors; dispensing 6 coins per second
- ✓ Huge range of potential payout configuration
- ✓ Accepts US .05, .10, .25, .50, \$1 coins
- ✓ Accepts Canadian .05, .10, .25, \$1, \$2 coins
- ✓ High capacity \$360+ allows elimination of bill change machines
- ✓ Temperature range of -25°C to +80 °C



Intuitive menu structure and large backlit LCD for ease of programming.



Henri programming module, Operators can download new programs.



Payout module offers 3 independent & parallel working motors. Pays out up to 6 coins per second. Built-in redundancy in case one motor fails, 4 tubes are still available.



Robust 6-tube design. Accepts from 5 cent up-to \$2 Canadian with 1742 possible tube combinations.

## Consumer Features

- ✓ 6 self-replenishing tubes keep the unit ready to make change
- ✓ High \$1 Capacity, excellent for recycling \$5s
- ✓ Speed and reliability keep consumers flowing through
- ✓ Wide temp range keeps the unit in service even in extreme environments
- ✓ Supports wide range of tokens, up to 33 mm in diameter, bring fun to vending

## Service Features

- ✓ Graphical display shows:
  - Tube contents
  - Changer status
  - Current activity
- ✓ Menus for configuring, auditing, running built in diagnostics
- ✓ The display is a backlit LCD visible in the full range of lighting from total darkness to direct sun light
- ✓ Can examine actual sensor readings for debugging
- ✓ Allows full tube configuration
- ✓ World class download of new coin sets or software using the "Henri" module with its full screen for verification
- ✓ Full support of Currenza® Bill Recyclers including DEX accountability



Currenza® c <sup>2</sup> Coin Changer Specifications	
Coins Accepted	US: .05, .10, .25, .50, \$1 CAN: .05, .10, .25, \$1, \$2
Acceptance Rate	95% Spec, 98% typical
Operating temperature	-25°C to +80 °C / -13°F to +176 °F
Number of tubes	6
Coins Dispensed	Tubes exist for every accepted coin
Dispense rate	2 coins per second per motor.
Dispense Motors	3
Protocol	MDB
Display	Back lit LCD
Weight	3.8 lbs
Operating Voltage	22 to 43 Volts (AC or DC)

Distributed by  
**Hemisphere West Europe Ltd**  
Ty Bryneirin  
Samau,  
Llandysul  
Ceredigion  
SA44 6QR  
UK

Tel: +44 (0) 1239 654157  
Fax: +44 (0) 1239 654742  
e-mail: [sales@hwieurope.com](mailto:sales@hwieurope.com)  
Web: [www.hwiglobal.com](http://www.hwiglobal.com)

**HW**e  
Hemisphere West Europe  
UNATTENDED PAYMENT SPECIALISTS